



# Water Resistant Digital Thermometer With 140mm Probe

## Product Images



## Short Description

---

Water Resistant Digital Thermometer With 140mm Probe

## Description

---

The TFA thermometer probe is a simple unit, which will measure a wide range of temperatures from -50°C to 200°C.

The probe itself measures 140mm, and can be used in liquids, powders and semi-solids.

The unit is splash proof and carries an IP55 rating. There is an auto-off function after 10 minutes, to save on battery life.

A protective cap is supplied for the probe.

### Technical Specification

- >Temperature Range: -50°C to 200°C
- >Accuracy: +/-1°C between -10°C to 100°C **or** +/-2°C between -50°C to -10°C and 100°C to 200°C
- >Penetration Probe: 140mm
- >IP55
- >Measurement: °C
- >Dimensions: W 25 x D 17 x L 235
- >Battery: 1 x LR44
- >Battery Life: 12-18 months
- >Warranty: 1 Year
- >Manufacturer: TFA

## Additional Information

Brand	TFA Dostmann
Humidity	no
Temperature	yes
Temperature Sensor	no
Wet Bulb	no
Clip-On	no
Humidity Range	no
Probe Type	Penetration Probe
Auto Switch Off	yes
Hold Function	no
HACCP Compliant	yes
Min/Max Readings	no
Warranty	1 Year
Calendar	no
Calibration	Can Be Calibrated
Dew Point	no
Weatherproof	no
Water Resistant	no
Waterproof	no
Solar Light	no
Protective Case	no
Probe Temperature	yes
Handheld	yes
Dual Display	no
Cabled Probe	no
Temperature Resolution	+/- 1°C

Probe Length	140mm
Response Time In Seconds	10
Humidity Sensor	no
Comfort Level Indicator	no
Moon Phase	no
Backlight	no
Indoor Temperature	no
Indoor Humidity	no
Clock	no
Transmission Range	no
Transmission Frequency	no
Temperature Range	-50 to 300°C
Temperature Accuracy	+/- 1°C
Measuring Units	°C
Humidity Resolution	no
Humidity Accuracy	no
Power	Battery
IP Rating	IP55
Outdoor Temperature	no
Size : Depth	2.5cm
PC Connection	no
Touch Screen	no
Min/Max Reset	no
Dew Point Alarm	no
High/Low Humidity Alarm	no
High/Low Temp Alarm	no
Outdoor Humidity	no

Size : Height	23.5cm
Size : Width	1.5cm

## Additional Options

---

<b>Temperature Calibration Certificate</b>	2 Point Temperature Calibration (0°C / 60°C)
	2 Point Temperature Calibration (please specify temperature points)
	1 Point Temperature Calibration (0°C)