



# **Digital Professional Thermo-Hygrometer**

# **Product Images**



### Description

This pen-style unit simultaneously displays the temperature and humidity readings, with the added function of being able to display minimum and maximum readings.

The metal housing incorporates a handy pocket clip, meaning the unit can be handy at all times.

#### **Technical Specification**

- Temperature Range: -20 °C to 60 °C
- Humidity Range: -20% to 95%
- Accuracy: +/-1°C
- Measurement: °C and °F
- Dimensions: H 160 x W 17mm
- Battery: 1 x AAA battery (included)
- Warranty: 1-Year
- Manufacturer: TFA

## **Additional Information**

Brand     IFA Dostmann       Humidity     yes       Temperature     yes       Temperature Sensor     no       Wet Bulb     no       Clip-On     yes       Humidity Range     20% to 95%       Probe Type     no       Auto Switch Off     no       Hold Function     no       HACPC Compliant     no       Maranty     1Year       Yearanty     1Year       Calendar     no       Yeare Point     no       Vaterproof     no       Waterproof     no       Yeare Point     no </th <th>Drand</th> <th></th>	Drand	
TemperatureyesTemperature SensornoWet BulbnoUte BulbyesHundity Range20% to 95%Probe TypenoAuto Switch OffnoHudid FunctionnoHold FunctionnoMarXeadingsyesMarAnty19karaAranty19karaCalendarnoGaldraftnoProbertynoCalendarnoMarkensportnoMatherproofnoWater ResistantnoNotare ResistantnoProberty ResistantnoProberty ResistantnoHondhaldyesHondhaldyesProberty ResistantnoProberty	Brand	TFA Dostmann
Temperature SensornoVet BulbnoClip-OnyesHumidty Range20% to 95%Probe TypenoAuto Switch OffnoHudf LuctionnoHACCP CompliantnoMin/Max ReadingsyesVarranty1 YearCalibrationnoCalibrationnoGuider SensornoMarkengenoSensornoCalibrationnoMarkengenoSensornoSensornoMatherproofnoWater ResistantnoSolar LightnoProbe TemperaturenoHondbeldnoProbe TemperaturenoMutald LightnoHondbeldnoProbe TemperaturenoMutald LightnoHondbeldno <t< td=""><td>Humidity</td><td>yes</td></t<>	Humidity	yes
Wet BulbnoClip-OnysHumidity Range20% to 95%Probe TypenoAuto Switch OffnoAuto Switch OffnoHold FunctionnoHACP CompliantysMin/Max ReadingsysClendarnoAuto Switch OffnoClendarnoAuto SupportnoAuto SupportnoMatherproofnoWater ResistantnoVater ResistantnoSolar LightnoProbe TemperaturenoHondel CalipsapportnoAuto SupportnoStart SupportnoStart SupportnoSupportnoMatherproofnoSupport	Temperature	yes
Clip-OnyesHumidity Range20% to 55%Humidity RangenoArobe TypenoAuto Switch OffnoHold FunctionnoHACCP CompliantyesMir/Max ReadingsyesCalendarnoCalendarCal Be CalibratedPow PointnoWater ResistantnoVater ResistantnoSolar LightnoProtective CasenoProtective CasenoProtective CasenoProtective CasenoProtective CasenoProtective CasenoProtective CasenoPound DiagnationmoProtective CasenoPound DiagnationnoProtective CasenoPound DiagnationmoProtective CasenoPound DiagnationmoPound Diagnationmo <t< td=""><td>Temperature Sensor</td><td>no</td></t<>	Temperature Sensor	no
Humidity Range20% to 95%Probe TypenoAuto Switch OffnoHunditonnoHold FunctionnoHACCP CompliantnoMin/Max ReadingsyesVarranty1 VaraCalendarnoCalibrationcon BecalibratedPow PointnoWatherproofnoWater ResistantnoSolar LightnoProtective CasenoHundheldyesLudapholdnoProbe Type Type Type Type Type Type Type Typ	Wet Bulb	no
Probe TypenoAuto Switch OffnoHold FunctionnoHACCP CompliantnoMin/Max ReadingsyesWarranty1 YearCalendarnoCalibrationCan Be CalibratedDew PointnoWater ResistantnoVater ResistantnoSolar LightnoProbe TemperaturenoProbe TemperaturenoHandheldyesCalon LightnoProbe TemperaturenoMater ResistantnoProbe TemperaturenoProbe TemperaturenoMatheldyesMatheldyesMatheldnoMater ResistantnoMatheldnoMatheldnoMatheldnoMatheldyesMatheldnoM	Clip-On	yes
Auto Switch OffnoHold FunctionnoHACCP CompliantnoMin/Max ReadingsyesWarranty1 YearCalendarnoCalendarnoCalibrationCan Be CalibratedDew PointnoWater ResistantnoVatergroofnoSolar LightnoProbec TemperaturenoHandheldyesLandheldyesAuto SpalaynoSolar LightnoProbec TemperaturenoHandheldyesLandheldyesSolar LightnoHandheldyesHandheldyesHandheldnoHandheldnoHandheldyesHandheldnoHandheldnoHandheldyesHandheldno <trr>HandheldnoHandh</trr>	Humidity Range	20% to 95%
Hold FunctionnoHACP CompliantnoMin/Max ReadingsyesWarranty1 VarrantyCalendarnoCalendarnoCalibrationCan Be CalibratedDew PointnoWater ResistantnoSolar LightnoProtective CasenoProtective CasenoHandheldyesLightspinnoProtective CasenoSolar LightnoProtective CasenoHandheldyesCable DaylenoSolar LightnoSolar Lightno<	Probe Type	no
HACCP CompliantnoMin/Max ReadingsyesWarnany1 VearCalendarnoCalibrationCan Be CalibratedDew PointnoWatherproofnoWater ResistantnoSolar LightnoProbe TemperaturenoProbe TemperaturenoJandheldyesLight SpainnoProbe TemperaturenoMater ProbenoMater ProbenoProbe TemperaturenoMater ProbenoMater ProblemnoMater ProblemnoMa	Auto Switch Off	no
Min/Max ReadingsyesWarranty1 VearCalendarnoCalendarCalendarDew PointnoWeatherproofnoWaterproofnoSolar LightnoProtective CasenoHandheldyesDau DisplaynoSolar LightnoMaterproofnoProtective CasenoMatherednoSolar LightnoMatherednoSolar LightnoMathered <td>Hold Function</td> <td>no</td>	Hold Function	no
Waranty1 YearCalendarnoCalibrationCan Be CalibratedDew PointnoWeatherproofnoWater ResistantnoYolder LightnoProtective CasenoHandheldyeaDual DisplaynoCabled ProbenoNater StatenoState Stat	HACCP Compliant	no
CalendarnoCalendarCan Be CalibratedDew PointnoWeatherproofnoWater ResistantnoVaterproofnoSolar LightnoProtective CasenoHandheldysaDual DisplaynoCabled ProbenoSolar LightnoSolar Light <td>Min/Max Readings</td> <td>yes</td>	Min/Max Readings	yes
CalibrationCan Be CalibratedDew PointnoWeatherproofnoWater ResistantnoWaterproofnoSolar LightnoProtective CasenoHandheldysaDual DisplaynoCabled ProbenoNonoCabled ProbenoNonoCabled ProbenoNonoCabled ProbenoNonoCabled ProbenoNonoCabled ProbenoNonoCabled ProbenoNonoCabled ProbenoNonoNonoNonoCabled ProbenoNo <td< td=""><td>Warranty</td><td>1 Year</td></td<>	Warranty	1 Year
Dew PointnoWeatherproofnoWater ResistantnoWaterproofnoSolar LightnoProtective CasenoHandheldysaDual DisplaynoCabled Probeno	Calendar	no
WeatherproofnoWater ResistantnoWaterproofnoSolar LightnoProtective CasenoProbe TemperaturenoDual DisplaynoCabled Probeno	Calibration	Can Be Calibrated
Water ResistantnoWaterproofnoSolar LightnoProtective CasenoProbe TemperaturenoMandheldyesDual DisplaynoKabled Probeno	Dew Point	no
WaterproofnoSolar LightnoProtective CasenoProbe TemperaturenoHandheldyesDual DisplaynoKabled Probeno	Weatherproof	no
Solar LightnoProtective CasenoProbe TemperaturenoHandheldyesDual DisplaynoAbled Probeno	Water Resistant	no
Protective CasenoProbe TemperaturenoHandheldyesDual DisplaynoCabled Probeno	Waterproof	no
Probe TemperaturenoHandheldyesDual DisplaynoCabled Probeno	Solar Light	no
HandheldyesDual DisplaynoCabled Probeno	Protective Case	no
Dual Display no   Cabled Probe no	Probe Temperature	no
Cabled Probe no	Handheld	yes
	Dual Display	no
Temperature Resolution +/- 1°C	Cabled Probe	no
	Temperature Resolution	+/- 1°C

Humidity Sensor	no
Comfort Level Indicator	no
Moon Phase	no
Backlight	no
Indoor Temperature	yes
Indoor Humidity	yes
Clock	no
Transmission Range	no
Transmission Frequency	no
Temperature Range	-20 to 60°C
Temperature Accuracy	+/- 1°C
Measuring Units	%, °C & °F
Humidity Resolution	1%rh
Humidity Accuracy	no
Power	Battery
Outdoor Temperature	no
Size : Depth	2cm
PC Connection	no
Touch Screen	no
Min/Max Reset	yes
Dew Point Alarm	no
High/Low Humidity Alarm	no
High/Low Temp Alarm	no
Outdoor Humidity	no
Size : Height	16cm
Size : Width	2cm